

PK 4100 Compact

Technical Data

PK 4100 Compact

Max. lifting moment	38.5 kNm	28386 ft.lbs
Max. lifting capacity (CE)	- kg	- lbs
Max. lifting capacity	990 kg	2180 lbs
Max. hydraulic outreach	8.4 m	27 ' 7 "
Max. mechanical outreach	8.4 m	27 ' 7 "
Max. outreach (with fly jib)	- m	0 ' -0 "
Slewing angle	377 °	

Standard Cranes

Slewing angle	4.4 kNm	3244 ft.lbs
Outreach	5.8 m	19 ' 0 "
Stabilizer spread standard	1.9 m	6 ' 3 "
Stabilizer spread max.	3.5 m	11 ' 6 "
Fitting space required (min.)	0.46 m	1 ' 6 "
Fitting space required (max.)	0.506 m	1 ' 8 "
Width folded	2.0 m	6 ' 7 "
Operating pressure	200 bar	2900 psi
Recommended pump capacity	15 l/min	
Dead weight standard crane	635 kg	1400 lbs

PK 4100 A

<i>hydraulic</i>		
Outreach	Capacity	
3,3 m 10 ' 10 "	990 kg	2180 lbs
4,5 m 14 ' 9 "	870 kg	1920 lbs
5,8 m 19 ' 0 "	660 kg	1460 lbs

PK 4100 B

<i>hydraulic</i>		
Outreach	Capacity	
3,3 m 10 ' 10 "	990 kg	2180 lbs
4,5 m 14 ' 9 "	860 kg	1900 lbs
5,8 m 19 ' 0 "	650 kg	1430 lbs
7,1 m 23 ' 4 "	510 kg	1120 lbs

PK 4100 C*hydraulic*

Outreach

Capacity

3,3 m	10 ' 10 "	990 kg	2180 lbs
4,5 m	14 ' 9 "	820 kg	1810 lbs
5,8 m	19 ' 0 "	620 kg	1370 lbs
7,1 m	23 ' 4 "	490 kg	1080 lbs
8,4 m	27 ' 7 "	420 kg	930 lbs