

<b>PK 2700 Compact</b>
------------------------

**Technical Data**

**PK 2700 Compact**

Max. lifting moment	28.6 kNm	21087 ft.lbs
Max. lifting capacity (CE)	750 kg	1650 lbs
Max. lifting capacity	750 kg	1650 lbs
Max. hydraulic outreach	6.2 m	20' 4"
Max. mechanical outreach	- m	0' -0"
Max. outreach (with fly jib)	- m	0' -0"
Slewing angle	360 °	

**Standard Cranes**

Slewing angle	2.5 kNm	1843 ft.lbs
Outreach	5.2 m	17' 1"
Stabilizer spread standard	1.6 m	5' 3"
Stabilizer spread max.	2.7 m	8' 10"
Fitting space required (min.)	0.48 m	1' 7"
Fitting space required (max.)	0.48 m	1' 7"
Width folded	1.70 m	5' 7"
Operating pressure	200 bar	2900 psi
Recommended pump capacity	8 l/min	-
Dead weight standard crane	370 kg	820 lbs

**PK 2700 A**

<i>hydraulic</i>		
Outreach	Capacity	
3,0 m 9' 10"	750 kg	1650 lbs
4,1 m 13' 5"	540 kg	1190 lbs
5,2 m 17' 1"	400 kg	880 lbs

**PK 2700 B**

<i>hydraulic</i>		
Outreach	Capacity	
3,0 m 9' 10"	730 kg	1610 lbs
4,1 m 13' 5"	510 kg	1120 lbs
5,2 m 17' 1"	380 kg	840 lbs
6,2 m 20' 4"	280 kg	620 lbs